

Name: Jared Tebo Date: January 2014 Track / City: Ohio RC Factory Event: 2014 CRCRC

Front Suspension

4.8mm Ball Stud: UM128 (Std) UMW508 (+2mm High Mount)

Camber: -2°

Upper Spacer: 1 mm

4.8mm Ball Stud Spacer: 1 mm

Axle Spacer: Out ___ mm In ___ mm

Wheel Hub: ___ mm

4.8mm Ball Stud: LA246 (-1mm Low Mount) 97050M (Std)

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 0 mm

Toe: In Out 0°

Tie Rod: _____

Front Bulkhead Weight Placement: None Bulkhead Inside ___ oz ___ g On the skid plate ___ oz ___ g

Caster: 25° Spacer: 30° 0.5 1.0 None 0° 2° 4° OUT (Narrow)

Caster Block position: IN (wide/Std) OUT (Narrow)

Axle Height Spacer: 0 mm 1.5 mm

Front Axle: UM569 (RB6) UM506 (RB5)

Wheelbase: F: 1 mm R: 0 mm

Comments: Ackerman arrow pointing back

Rear Suspension

Sus Holder Spacer: F 0.5 1.0 None R 0.5 1.0 None

Anti-Squat: ___ °

4.8mm Ball Stud: UM129 UMW508 (+2mm High Mount) 97050M UM128 (Std)

Sway Bar: None ___ mm

Camber: -2°

Upper Spacer: 1 mm

Wheelbase: F: 0 mm R: 2 mm

Universal Swing Shaft: 65.5

Axle Spacer: Out ___ mm In ___ mm

Arm: UM713 UM521 UM566 UM521-1 UM503

Rear Hub Toe: 0° 0.5° 1° UM519 UM519-2 Alu (UMW516) Alu (UMW704)

RR: Upper Spacer: 1 mm

Lower Sus Holder: Normal RF Aluminum(Opt) UMW511+UMW512 RM UMW705+UMW706: MM UMW705+UMW707: a/b out

Wide RF2 UMW514+UMW515

Motor Position: Rear Motor Midship Motor

Diff.: Gear Diff. # _____ Ball Diff.

Comments: _____

Shock

Shock Piston: drilled 4x1.3 drilled 4x1.3

Shock Oil: #35 #30

Shock Spring: pink gold

Limiters: in out mm in out mm

Shock Length(A): ___ mm ___ mm

Shock Length(B): 20 mm 27 mm

O-ring: clear x-ring clear x-ring

Ball End type: Front: S M L
 Rear: S M L

aluminum shock caps

Battery Placement:

Comment: servo/small gap/battery/sp eedo

Front Rear

Foam: Front Rear None

Chassis

F: 24 mm Ride Height R: 24.5 mm

Battery Type

Straight Separate Short

Type: Orion 4000

Other

Motor: Orion VST2 7.5
ESC: Orion R10 pro
Pinion/Spur: 21/76

Track Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- BlueGroove
- Clay
- Dusty

Wing

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Wing Mount: Narrow Wide
- Wing Angle: 4° 7° 10°
- Lip: middle line

Tire

Front: AKA Typo Compound: Clay Insert: red evo Wheel: evo

Rear: AKA Typo Compound: Clay Insert: red evo Wheel: evo

Comment: buggy grip

Comment

all lunsford titanium screws. chassis tape. RSx servo

Editable by Arn0 at Petitr.com