

Name _____ Date _____ Truck / City _____ Event _____

Front Suspension:

4.8mm Ball Stud:
 UM128
 UMW508 (+2mm High Mount)

Upper Spacer: _____ mm

Shock Mount:
 IN
 OUT

Camber: _____ °

Axle Spacer:
 Out _____ mm

Caster Block:
 IN (wide/Std)
 OUT (Narrow)

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M

Ackerman Steer Spacer: _____ mm

Bump Steer Spacer: _____ mm

Axle Height Spacer:
 Up
 Down

Toe: In Out _____ °

Sus Mount:
 UM502
 UM567
 UM721

Caster:
 25°
 30°

Spacer:
 0.5
 1.0
 None

Wheelbase: Long Middle Short

Comments: _____

Rear Suspension:

Sus Holder Spacer:
 F 0.5 1.0 None
 R 0.5 1.0 None

Anti-Squat: _____ °

Sway Bar: None _____ mm

Upper Spacer: _____ mm

Wheelbase:
 F: _____ mm
 R: _____ mm

Lower Sus Holder:
 Normal RF RF2
 Aluminum(Opt) Front _____ Rear _____

Upper Spacer: _____ mm

Upper Spacer: UM788 UM706

Upper Spacer: _____ mm

Comments: _____

Drive:
 Rear Motor
 Midship Motor

Diff:
 Gear Diff # _____
 Ball Diff _____

Shock:

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ out _____	mm _____ mm _____	in _____ out _____	mm _____ mm _____
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Normal	<input type="checkbox"/> Alu(UM719)	<input type="checkbox"/> Normal	<input type="checkbox"/> Alu(UM719)
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

Chassis:

Battery Placement: Front Rear

Weight Placement:
 No Screw
 Screw

F _____ mm Ride Height: R _____ mm

Track Conditions:

Composition: _____
 Surface: _____
 Traction: _____
 Comments: _____

Body: _____

Tire:

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____
Traction Compound:	_____	_____

Electronics:

Motor: _____
 Pinion/Spur: _____
 Battery: _____
 ESC: _____
 Radio: _____
 Servo: _____
 Throttle/Brake: _____
 E PA: _____ Expo: _____
 Initial brake: _____
 Drag brake: _____
 Throttle profile: _____
 Steering expo: _____
 Steering speed: _____

Material:

Screw: Steel Titanium
 Servo Horn: Normal Rigid(UM717)
 Pinion Gear: Steel Aluminium
 Shock Ring: O-ring X-ring Red Clear

Comment: _____

