ULTIMA SC6 SET UP SHEET

KYOSHO — THE FINEST RADIO CONTROL MODELS

Name	Date	Track / City	Event
Jared Tebo	December 2014	The Plex Omaha, NE	JC Indoor Nats Final

Front Suspension



Upper Spacer: 1 mm

4.8mm Ball Stud:
- [x] UM128 (Std)
- [ ] UMW508 (+2mm High Mount)

Camber: -1° (- / +)

Shock Mount: [1] [2] — [ ] IN [x] OUT

Caster Spacer: [x] 25° [ ] 30° — [ ] 0.5 [ ] 1.0 [x] None

Caster Block: [ ] IN (wide/Std) [x] OUT (Narrow) ____°

Axle Spacer: [x] Out ____ mm

Forward/Reverse: [ ] Forward (Std) [x] Reverse

Upper Spacer: 1 mm

4.8mm Ball Stud: [ ] LA246 (-1mm Low Mount) [x] UM129 (Std)

Ackerman Steer Spacer: 0 mm

Bump Steer Spacer: 0 mm

Axle Height Spacer: [ ] Up [x] Down

Toe: [ ] In [ ] Out 0°

Sus Mount: [ ] UM503 [ ] UM567 [x] UM721

Wheelbase: [ ] Long [x] Middle [ ] Short

Comments:

Rear Suspension



Sus Holder Spacer:
F [ ] 0.5 [ ] 1.0 [x] None
R [x] 0.5 [ ] 1.0 [ ] None



Type-B (UM519)
Type-B2 (UM519-2)

Anti-Squat: ____°

Sway Bar: [x] None [ ] ____mm

Upper Spacer: 2 mm



Wheelbase: F: 1 mm R: 5 mm

Camber: -1° (- / +)



Rear Hub add Toe:
- [ ] 0°Type-B (UM519)
- [ ] 0°Type-B2 (UM519-2)
- [x] 0°Alu (UMW704-0)
- [ ] 0.5°Alu (UMW704-05)
- [ ] 1°Alu (UMW704-1)

Axle Spacer:
- [ ] Out ____ mm
- [ ] In ____ mm



[ ] UM788 [ ] UM706

Lower Sus Holder:

Normal: [ ] RF [ ] RF2 — Aluminum(Opt): Front D in Rear C in

Upper Spacer: 1 mm

Comments: new inner drilled hole. 28.5 mm from sway bar hole

Drive

- [ ] Rear Motor
- [x] Midship Motor

Diff

- [ ] Gear Diff. #
- [x] Ball Diff.

Shocks

	Front	Rear
Shock Piston:	1.35x5	1.35x5
Shock Oil:	#40	#35
Shock Spring:	Orange	Red
Limiters:	in ____ mm / out ____ mm	in ____ mm / out ____ mm
Shock Length(A):	27 mm	33.5 mm



Shock Top Type: [ ] Nomal [x] Alu(UM719)

5.8mm Ball End:
Front: [ ] S [x] M [ ] L
Rear: [ ] S [x] M [ ] L

Body

Editable by Arn0 at Petitrc.com

JC High Flow

Material

- Screw: [ ] Steel [x] Titanium
- Servo Hone: [x] Nomal [ ] Rigid(UM717)
- Pinion Gear: [x] Steel [ ] Aluminium
- Shock Ring: [ ] O-ring [ ] X-ring [ ] Red [x] Clear

Chassis

Weight Placement

servo/big gap/receiver/speedo/saddle battery sideways



F 30 mm — Ride Height: — R 28 mm

Tires

	Front	Rear
Tire:	AKA Typo Clay	AKA Typo Clay
Inserts:	AKA Black Wide	AKA Black Wide
Wheel:	AKA	AKA
Traction Compound:	Liquid Wrench	

Comment :

Battery Placement

Electronics

- Motor: Orion 6.5
- Pinion/Spur: 17/82
- Battery: Orion 5500
- ESC: Orion R10.1 Pro
- Radio: KO EX-1
- Servo: KO RSx Response
- Throttle/Brake:
- EPA: ____ Expo: ____
- Initial brake: ____
- Drag brake: ____
- Throttle profile: ____
- Steering expo: ____
- Steering speed: ____

Arn0