


Name \_\_\_\_\_ Date \_\_\_\_\_ Truck / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension:



Toe:  In  Out \_\_\_\_\_°  
 Sus Mount:  UM502  
 UM567  
 UM721

Upper Spacer: \_\_\_\_\_ mm




4.8mm Ball Stud:  
 UM128  
 UMW508 (+2mm High Mount)

Shock Mount:  
 IN  
 OUT



Camber: \_\_\_\_\_°




Upper Spacer: \_\_\_\_\_ mm

4.8mm Ball Stud:  
 LA246 (-1mm Low Mount)  
 97050M

Ackerman Steer Spacer: \_\_\_\_\_ mm

Bump Steer Spacer: \_\_\_\_\_ mm



Axle Spacer: \_\_\_\_\_ mm

Out \_\_\_\_\_ mm

Axle Height Spacer:  
 Up  
 Down


Caster Spacer:  
 25°  0.5  
 30°  1.0  
 None  None

Caster Block:  
 IN (wide/Std)  
 OUT (Narrow)


Wheelbase:  Long  Middle  Short

Comments: \_\_\_\_\_

### Rear Suspension:



UM788  UM706




Upper Spacer: \_\_\_\_\_ mm


Sus Holder Spacer:

F  0.5  1.0  None  
 R  0.5  1.0  None

Anti-Squat: \_\_\_\_\_°  
 Sway Bar:  None  \_\_\_\_\_mm




Upper Spacer: \_\_\_\_\_ mm



Wheelbase:

F: \_\_\_\_\_ mm  
 R: \_\_\_\_\_ mm



Lower Sus Holder:

Normal Aluminum(Opt)  
 RF  RF2 Front \_\_\_\_\_ Rear \_\_\_\_\_

Camber: \_\_\_\_\_°

Axle Spacer:

Out \_\_\_\_\_ mm  
 In \_\_\_\_\_ mm

Rear Hub

0° Type-B (UM519)  
 0° Type-B2 (UM519-2)  
 0° Alu (UMW704-0)  
 0.5° Alu (UMW704-05)  
 1° Alu (UMW704-1)

### Drive:


Rear Motor  
 Midship Motor

### Diff:

Gear Diff # \_\_\_\_\_  
 Ball Diff \_\_\_\_\_

### Shock:

	Front		Rear	
Shock Piston:	_____	_____	_____	_____
Shock Oil:	# _____	# _____	# _____	# _____
Shock Spring:	_____	_____	_____	_____
Limiters:	in _____ out _____	mm _____ mm _____	in _____ out _____	mm _____ mm _____
Shock Length(A):	_____ mm	_____ mm	_____ mm	_____ mm
Shock Top Type:	<input type="checkbox"/> Normal	<input type="checkbox"/> Alu(UM719)		
5.8mm Ball End:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L		Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	



### Chassis:

Battery Placement: \_\_\_\_\_  
 Front Rear

Weight Placement  
 No Screw  Screw  
 F \_\_\_\_\_ mm Ride Height: R \_\_\_\_\_ mm

Tire: Front \_\_\_\_\_ Rear \_\_\_\_\_

Tire: \_\_\_\_\_  
 Inserts: \_\_\_\_\_  
 Wheel: \_\_\_\_\_  
 Traction Compound: \_\_\_\_\_

Comment: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

### Track Conditions:

Composition: \_\_\_\_\_  
 Surface: \_\_\_\_\_  
 Traction: \_\_\_\_\_  
 Comments: \_\_\_\_\_

### Electronics:

Motor: \_\_\_\_\_  
 Pinion/Spur: \_\_\_\_\_  
 Battery: \_\_\_\_\_  
 ESC: \_\_\_\_\_  
 Radio: \_\_\_\_\_  
 Servo: \_\_\_\_\_  
 Throttle/Brake: \_\_\_\_\_  
 E PA: \_\_\_\_\_ Expo: \_\_\_\_\_  
 Initial brake: \_\_\_\_\_  
 Drag brake: \_\_\_\_\_  
 Throttle profile: \_\_\_\_\_  
 Steering expo: \_\_\_\_\_  
 Steering speed: \_\_\_\_\_

### Body:

### Material:

Screw:  Steel  Titanium  
 Servo Horn:  Normal  Rigid(UM717)  
 Pinion Gear:  Steel  Aluminium  
 Shock Ring:  O-ring  X-ring  Red  Clear