

Name \_\_\_\_\_ Date \_\_\_\_\_ Track / City \_\_\_\_\_ Event \_\_\_\_\_

### Front Suspension

**Upper Spacer:** \_\_\_\_\_ mm

**Shock Tower:** \_\_\_\_\_ mm

**Toe:**  In  Out \_\_\_\_\_ °

**Tie Rod:** \_\_\_\_\_ mm

**Front Bulkhead Weight Placement:**

- None
- Bulkhead Inside \_\_\_\_\_ oz \_\_\_\_\_ g
- On the skid plate \_\_\_\_\_ oz \_\_\_\_\_ g \* 1oz=28g

**4.8mm Ball Stud: Camber:** \_\_\_\_\_ °

- UM128(Std.)
- UMW508 (+2mm High Mount)

**4.8mm Ball Stud Spacer:** \_\_\_\_\_ mm

**Caster:** \_\_\_\_\_ °

- 25°
- 30°

**Caster Block:** \_\_\_\_\_

- 0.5
- 0°
- 1.0
- 2°
- None
- 4°

**AL. Steering Support:**

- None
- UMW724

**4.8mm Ball Stud:**

- LA246 (-1mm Low Mount)
- 97050M (Std)

**Ackerman Steer Spacer:** \_\_\_\_\_ mm

- UMW701 Aluminum ST Plate
- UMW702 Aluminum Clank Arm

**Wheel Hub:**

- UM569 / Std
- UM506

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**Comments:** \_\_\_\_\_

### Rear Suspension

**Shock Tower:** \_\_\_\_\_ mm

**RR:** \_\_\_\_\_ mm

**Mid:** \_\_\_\_\_ mm

**4.8mm Ball Stud:**

- UM129
- UMW508 (+2mm High Mount)
- 97050M
- UM128(Std.)

**Upper Spacer:** \_\_\_\_\_ mm

**Anti-Squat:** \_\_\_\_\_ °

**Camber:** \_\_\_\_\_ °

**Universal Swing Shaft:** \_\_\_\_\_ mm

**Lower Sus. Holder:**

- Plastic
  - RF
  - RF2L
  - RF2
- Option
  - UMW511GM (RF/Alu)

**Sus Holder Spacer:**

F:  0.5  1.0  None

R:  0.5  1.0  None

**Upper Spacer:** \_\_\_\_\_ mm

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**Wheelbase:** F: \_\_\_\_\_ mm R: \_\_\_\_\_ mm

**Sway Bar:**  None  \_\_\_\_\_ mm

**Drive Hub :**

- 4mm (TFW113)
- 4.5mm (LAW30GM/Std.)
- 5.2mm (UMW523)

**Axle Spacer:**

- Out \_\_\_\_\_ mm
- In \_\_\_\_\_ mm

**Rear Hub Carrier :**

- 0°Type-B (UM519)
- 0°Type-B2 (UM519-2)
- 0° Alu (UMW704-0)
- 0.5°Alu (UMW704-05)
- 1°Alu (UMW704-1)

**Diff.**

- Gear Diff. # \_\_\_\_\_
- Ball Diff.

### Shock

	Front	Rear
Shock Piston:	_____	_____
Shock Oil:	# _____	# _____
Shock Spring:	_____	_____
Limiters:	in _____ mm out _____ mm	in _____ mm out _____ mm
Shock Length(A):	_____ mm	_____ mm
O-ring:	_____	_____
Shock Top type:	<input type="checkbox"/> Alu(UM719/Std)	<input type="checkbox"/> UM753-1
Ball End type:	Front: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L	Rear: <input type="checkbox"/> S <input type="checkbox"/> M <input type="checkbox"/> L

### Battery Placement:

None  Screw

Front:   Rear:

Foam:  Front  Rear  None

### Transmission

- Rear Motor
- Mid-Ship 3 Gear
- Mid-Ship 4 Gear
- Mid-Ship Laydown

### Chassis

Stock  UM731

F \_\_\_\_\_ mm Ride Height: R \_\_\_\_\_ mm

### Battery Type

- Straight
- Separate
- Short

Type: \_\_\_\_\_

### Track Condition

- Smooth
- Bumpy
- Low Traction
- Med. Traction
- High Traction
- Wet
- Dry
- Sandy
- Soft Dirt
- Grass
- Blue Groove
- Clay
- Dusty

### Wing

Wing Mount :  Narrow  Wide

Wing Angle :  4°  7°  10°

Lip : \_\_\_\_\_

- Blast-S
- Blast-L
- Step-S
- Step-M
- Step-L
- Step 2.0
- Step 3.0
- Straight
- Round

### Tire

	Front	Rear
Tire:	_____	_____
Inserts:	_____	_____
Wheel:	_____	_____

### Other

Motor: \_\_\_\_\_

ESC: \_\_\_\_\_

Pinion/Spur: \_\_\_\_\_